

HBKU SS 250/25 Stainless Steel Hygienic Border Panel and Wall Protector on the Flooring

- Description** : Anti-bacterial, dirt and stain-resistant, easy-to-clean Stainless Steel Hygienic Border Panel and Wall Protector.
- Product Code** : **HBKUSS25025-000**, **HBKUSS25025-ID0 (internal corner)**, **HBKUSS25025-DD0 (external corner)**
HBKUSS25025-SSB (right-left end pieces)
- Areas of Use** : Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Oil, Food, Beverage, etc.)
Healthcare Industry (Hospitals, Laboratories, Pharmaceutical Manufacturing & Storage),
Chemical, Petrochemical, Automotive, Cosmetic Industry, Logistics and Transportation, Tourism,
Shopping Centers and Supermarkets, etc.
- Technical Specifications** : Bottom edges of walls; Radius rotation. ($r = 47,5 \text{ mm.} \sim \varnothing 95 \text{ mm}$)
Bonded with a special technique using stainless visco concrete composite with stainless visco
concrete filling reinforced with iron of class AISI 304 and AISI 316 L.
Resistant to oil, acids, cleaning chemicals, and medium and heavy impacts, complying with food
hygiene. Usage temperature range: $-40^{\circ}\text{C} / +80^{\circ}\text{C}$
- Fire Reaction Class** : Not flammable.
- Material** : Stainless hygienic composite bordure
- Color** : Stainless steel.
- Installation** : **As an adhesive;** VIBROSER H70 (Hybrid) MS Polymer based one-component adhesive with high ad-
hesion strength and ISEGA certification, appropriate for food and sanitation hygiene, and resistant
to acid and chemicals, is used. (H70 600 ml. Sausage Consumption Average $\sim 5 \text{ m.}$ adhesive)
As a joint sealant; VIBROSER S67 Neutral Silicone Mastic Sealant with ISEGA certification, approp-
riate for food and sanitation hygiene, which does not allow the reproduction of mold or fungus on
its surface, is used.
(S67 600 ml. Sausage Consumption Average $\sim 5 \text{ m.}$ joint consumption)
- Dimensions** : Height: 250 mm. Length: 1,000 mm. Thickness: 25 mm. Radius Diameter: [$r = 47,5 \text{ mm.} \sim \varnothing 95 \text{ mm}$]
- Weight** : HBKUSS25025-000; $\sim 17,000 \text{ kg/m.}$ HBKUSS25025-ID0 internal corner $\sim 3,500 \text{ kg/pc.}$ HBKUSS25025-DD0
external corner $\sim 2,500 \text{ kg/pc.}$ HBKUSS25025-SSB right-left end pieces $\sim 1,250 \text{ kg/pc.}$
- Packaging** : Product is shipped on pallets, within boxes or crates, depending on quantity, wrapped in nylon
shrink packages in the form of single packs.

