

Hexagonal Anti-Acid Tile

- Description** : It is produced in hexagonal form, dimensions of 100x115 mm, with **15,0 mm.** thickness, on the back to enhance the adhesion strength, edges with conical and natural joint providing nails, anti-slip surface to grades R9, R10, R11 and R12.
- Product Code** : **GRAUPK-10011515**
- Areas of Use** : Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Oil, Food, Beverage, etc.)
Healthcare Industry (Hospitals, Laboratories, Pharmaceutical Manufacturing & Storage),
Chemical, Petrochemical, Automotive, Cosmetic Industry, Logistics and Transportation, Tourism,
Shopping Centers and Supermarkets, etc.
- Material** : They are anti-bacterial, antistatic, non-porous, easy-to-clean products with low water absorption values and resistance to acids and chemicals.
Their surface does not allow reproduction of dirt or microorganisms.
Due to its size and form, hexagonal tile is even more resistant to impacts and heavy loads.
- Color** : **Grau Porphy**
- Dimensions** : **100x115x15,0 mm.**
- Weight and Packaging** : Box ~13,94 Kg/0,37 m² Palet ~1200 Kg/30,83 m² dispatched on nylon shrink wrapping pallets.
- Installation** : **VSEE** Vibration System XW1000 epoxy based adhesive and W13 epoxy based liquid grouting mortar application.
VSFE Vibration System flex adhesive and W13 epoxy based liquid grouting mortar application.
VSFF Vibration System flex adhesive and flex grouting mortar application.

