



## W13 A+B+C EPOXY BASED LIQUID GROUTING MORTAR

- Description** : It is a solvent-free, water-wipeable, A+B+C three component, epoxy-based RG2 grade adhesive and multi-purpose repair mortar with high adhesion strength developed for vibrating system tile applications in industrial facilities.
- Product Code** : **W13-0000LEDDABC**
- Areas of Use** : Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Oil, Food, Beverage, etc.)  
Healthcare Industry (Hospitals, Laboratories, Pharmaceutical Manufacturing & Storage),  
Chemical, Petrochemical, Automotive, Cosmetic Industry, Logistics and Transportation, Tourism,  
Shopping Centers and Supermarkets, etc.
- Method of Application** : It should be mixed for 3-4 minutes, by means of a hand mixer with low speed, until it becomes homogeneous. Combing and grouting are carried out with a steel and rubber trowel.
- Color** : **Beige**
- Weight and Packaging** : In plastic drums, A+B 28 Kg (Mixture A 20 Kg - Mixture B 8 Kg) on 114x114 Cm. 560 Kg/Pallet  
Shipped in boxes or on pallets depending on quantity.
- Shelf Life** : 1 year from the date of production if stored in its original unopened package, in a dry and moisture-free environment between +5 and +25°C. Avoid exposing to sunlight.

### W13 A+B EPOXY BASED LIQUID GROUTING MORTAR



### EPOXY C SPECIAL SILICONE SAND

