

BOTTOM-OUT STANDART SIPHON, ASEPTIC FLOOR DRAIN TRAP

Description	: It is a siphon-regulated, point-by-point wastewater evacuation product that can be cleaned to transfer wastewater formed in the installation facilities. This Drainage Systems product will prevent bacteria formation, which will create a precaution from wastewater installation to odor and pest input.
Product Code	: WSAC-30-F-11-00
Areas of Use	: Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Fat Food, Beverage, etc.) Health Sector (Hospital, Laboratory, Pharmaceutical Production-Storage), Chemistry, Petro-Chemistry, Automotive, Cosmetics, Logistics and Transportation, Tourism Sectors, Shopping Malls, and Supermarkets
Technical Specifications	: Aseptic (hermetic) Plate, bottom output, fixed siphon, flush mouse lock, height adjustment parts.
Dimensions	: 300 x 300 x 123 mm
Output Measure	: DN100 (Ø110 mm)
Plate Thickness	: 8,00 mm
Odor Retention Water Depth	: 60,00 mm
Solid Waste Holder Type	: Bucket type filter with a basket
Top Plate Hole Type	: Aseptic (hermetic) closed plate, oring seal
Material	: Complete AISI304 quality stainless steel product
Weight	: 8,10 kg
Packaging	: It is shipped in single packages with nylon shrink, in boxes, pallets, or cases, depending on the quantity.
Explanation	: Drainage systems made of AISI304 or AISI316 grade stainless steel, siphon and duct production are made on a standard or project basis.

