

BOTTOM-OUT STANDART SIPHON DRAIN TRAP

Description	: It is a siphon-regulated, point-by-point wastewater evacuation product that can be cleaned to transfer wastewater formed in the installation facilities. It will prevent bacteria formation, which will create a precaution from wastewater installation to odor and pest input.
Product Code	: WTAC-30-F-11-UM
Areas of Use	: Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Fat Food, Beverage, etc.) Health Sector (Hospital, Laboratory, Pharmaceutical Production-Storage), Chemistry, Petro-Chemistry, Automotive, Cosmetics, Logistics and Transportation, Tourism Sectors, Shopping Malls, and Supermarkets,
Technical Specifications	: With a fixed siphon, a graded pan with a mouse lock on the siphon, the first bend of the channel, and the second bend where the upper grill is placed, reinforced with a 14x14 mm section from the bottom, full iron plate, with anchorage and height adjustment parts.
Dimensions	: 300 x 300 x 200 mm
Output Measure	: DN100 (Ø110 mm)
Odor Retention Water Depth:	60,00 mm
Solid Waste Holder Type	: Bucket type strainer with basket.
Top Grid Type	: "U" Profile ladder type ("U" Profiles 2.00, outer frame 25x5 mm flat plate)
Material	: Completely made of AISI304 quality stainless steel, with the "U" profiles of the pan and top grate being 2.00 mm, the upper grate's outer frame is 25x5 mm.
Weight	: 9,30 kg
Packaging	: It is shipped in single packages with nylon shrink, in boxes, pallets, or cases, depending on the quantity.
Explanation	: Drainage systems made of AISI304 or AISI316 grade stainless steel, siphon and duct production are made on a standard or project basis.

