

HBKU SS 300/100 Stainless Steel Hygienic Border Panel and Wall Protector on the Flooring

Description	Anti-bacterial, dirt and stain-resistant, easy-to-clean Stainless Steel Iron-Reinforced Hygien Border Panel and Wall Protector.	ic
Product Code	HBKUSS300100-00, HBKUSS300100-ID (internal corner), HBKUSS300100-DD (external corner) HBKUSS300100SSB (right-left end pieces)	er)
Areas of Use	Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Oil, Food, Beverage, etc.) Healthcare Industry (Hospitals, Laboratories, Pharmaceutical Manufacturing & Storage), Chemicals, Petrochemicals, Automotive, Cosmetics, Logistics and Transportation, Tourism, Shopping Centers and Supermarkets, etc.	
Technical Specifications	Bottom edges of walls; Radius rotation. (r = 47,5 mm. ~ \emptyset 95 mm) Bonded with a special technique using stainless visco concrete composite with stainless visconcrete filling reinforced with iron of class AISI 304 and AISI 316 L. Resistant to oil, acids, cleaning chemicals, and medium and heavy impacts, complying with hygiene. Usage temperature range: -40 ° C / + 80 ° C	
Fire Reaction Class	Not flammable.	
Material	Stainless hygienic composite bordure	
Color	Stainless steel.	
Installation	As an adhesive; VIBROSER H70 (Hybrid) MS Polymer based one-component adhesive with h adhesion strength and ISEGA certification, appropriate for food and sanitation hygiene, and resistant to acid and chemicals, is used. (H70 600 ml. Sausage Consumption Average ~4 m. adhesive)	-
	As joint filler; S300 Neutral Silicone 300ml, which is suitable for food and health hygiene and does not form mold and fungus on its surface, provides high heat resistance up to 3000 (600 ml. Sausage Average ~6 m. joint consumption)	2
Dimensions	Height: 300 mm. Length: 1,000 mm. Thickness: 100 mm. Radius Diameter: [r = 47,5 mm. ~ 0.9	95 mm]
Weight	HBKUSS300100-00; ~62,000 kg/m. HBKUSS300100-ID internal corner ~16,500 kg/pc. HBKUSS300100-DD external corner~12,000 kg/pc. HBKUSS300100SSB right-left end pieces ~6,	,000 kg/pc.
Packaging	Product is shipped on pallets, within boxes or crates, depending on quantity, wrapped in nyl shrink packages in the form of single packs.	lon
produ	A Silicone 300mt, which does not the high heat resistance up to 300C ISI 304 or AISI 316 Stainless For bonding, food-safe ISEGA erified mastic sealant IRROSSR H70 with high adhesion strength Iron-Reinforcement 9 500 Neutral Silicone 300mt, which does not providing easy cleaning 500 Neutral Silicone 300mt, which does not produce bacteria and provides insulation against Leaks in joints, high heat resistance up to 300C Industrial floor	SSS300100SSB
		n

vibroser.com