

HBKU SS 750/50/Z300 Stainless Steel Hygienic Border Panel and Wall Protector on the Flooring

Description	: Anti-bacterial, dirt and stain-resistant, easy-to-clean Stainless Steel Iron-Reinforced Hygienic Border Panel and Wall Protector.
Product Code	 HBKUSS75050Z300, HBKU75050Z300ID (internal corner), HBKU75050Z300DD (external corner) HBKU750Z300-SSB (right-left end pieces)
Areas of Use	 Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Oil, Food, Beverage, etc.) Healthcare Industry (Hospitals, Laboratories, Pharmaceutical Manufacturing & Storage), Chemicals, Petrochemicals, Automotive, Cosmetics, Logistics and Transportation, Tourism, Shopping Centers and Supermarkets, etc.
Technical Specifications	 Bottom edges of walls; Radius rotation. (r = 47,5 mm. ~ Ø 95 mm) Bonded with a special technique using stainless visco concrete composite with stainless visco concrete filling reinforced with iron of class AISI 304 and AISI 316 L. Resistant to oil, acids, cleaning chemicals, and medium and heavy impacts, complying with food hygiene. Usage temperature range: -40 ° C / +80 ° C
Fire Reaction Class	: Not flammable.
Material	: Stainless hygienic composite bordure
Color	: Stainless steel.
Installation	 As an adhesive; VIBROSER H70 (Hybrid) MS Polymer based one-component adhesive with high adhesion strength and ISEGA certification, appropriate for food and sanitation hygiene, and resistant to acid and chemicals, is used. (H70 600 ml. Sausage Consumption Average ~3 m. adhesive)
	As joint filler; S300 Neutral Silicone 300ml, which is suitable for food and health hygiene and does not form mold and fungus on its surface, provides high heat resistance up to 300C. (600 ml. Sausage Average ~6 m. joint consumption)
Dimensions	: Height: 750 mm. Length: 1,000 mm. Thickness: 50/Z300 mm. Radius Diameter: [r = 47,5 mm. ~ 0 95 mm]
Weight	HBKUSS75050Z300; ~131,000 kg/m. HBKU75050Z300ID internal corner ~36,500 kg/pc. HBKU75050Z300DD external corner ~24,000 kg/pc. HBKU750Z300-SSB right-left end pieces ~12,000 kg/pc.
Packaging	: Product is shipped on pallets, within boxes or crates, depending on quantity, wrapped in nylon shrink packages in the form of single packs.
proc	Peterbalteria and provides insulation against in joints, high heat resistance up to 300C AISI 304 or AISI 316 Stainless For bonding, food-safe ISEGA Certified mastic sealant URDSEER H70 with high adhesion strength Ton-Reinforcement R47,5 radius produce bacteria and provides insulation against asis in joints, high heat resistance up to 300C Industrial floor Industrial floor



