

## Stainless Steel Floor Sink, Aseptic WSAC-23-PL-F-75

<b>Description</b>	: It is a siphon-regulated, point-by-point wastewater evacuation product that can be cleaned to transfer wastewater formed in the installation facilities. This Drainage Systems product will prevent bacteria formation, which will create a precaution from wastewater installation to odor and pest input.
<b>Product Code</b>	: <b>WSAC-23-PL-F-75</b>
<b>Areas of Use</b>	Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Fat Food, Beverage, etc.) Health Sector (Hospital, Laboratory, Pharmaceutical Production-Storage), Chemistry, Petro-Chemistry, Automotive, Cosmetics, Logistics and Transportation, Tourism Sectors, Shopping Malls, and Supermarkets
<b>Technical Specifications</b>	: Aseptic (hermetic) Plate, bottom output, antibacterial (detachable) siphon, height adjustment parts.
<b>Dimensions</b>	: 230 x 230 x 123 mm
<b>Output Measure</b>	: DN70 PVC (Ø75 mm)
<b>Plate Thickness</b>	: 8,00 mm
<b>Odor Retention Water Depth</b>	: 40,00 mm
<b>Solid Waste Holder Type</b>	: Bucket type filter with a basket
<b>Top Plate Hole Type</b>	: Aseptic (hermetic) closed plate, oring seal
<b>Material</b>	: Complete AISI304 quality stainless steel product
<b>Weight</b>	: 5,10 kg
<b>Packaging</b>	: It is shipped in single packages with nylon shrink, in boxes, pallets, or cases, depending on the quantity.
<b>Explanation</b>	: Drainage systems made of AISI304 or AISI316 grade stainless steel, siphon and duct production are made on a standard or project basis.

