

Stainless Steel Floor Sink, Circular Aseptic WSAC-23C-P-F-75

Description	: It is a siphon-regulated, point-by-point wastewater evacuation product that can be cleaned to transfer wastewater formed in the installation facilities. This Drainage Systems product will prevent bacteria formation, which will create a precaution from wastewater installation to odor and pest input.
Product Code	: WSAC-23C-P-F-75
Areas of Use	Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Fat Food, Beverage, etc.) Health Sector (Hospital, Laboratory, Pharmaceutical Production-Storage), Chemistry, Petro-Chemistry, Automotive, Cosmetics, Logistics and Transportation, Tourism Sectors, Shopping Malls, and Supermarkets
Technical Specifications	Circular aseptic (hermetic) Plate, bottom output, antibacterial (detachable) siphon, height adjustment parts.
Dimensions	: Ø230 x 123 mm
Output Measure	: DN70 PVC (Ø75 mm)
Plate Thickness	: 8,00 mm
Odor Retention Water Depth	: 40,00 mm
Solid Waste Holder Type	: Bucket type filter with a basket
Top Plate Hole Type	: Aseptic (hermetic) closed plate, oring seal
Material	: Complete AISI304 quality stainless steel product
Weight	: 4,40 kg
Packaging	: It is shipped in single packages with nylon shrink, in boxes, pallets, or cases, depending on the quantity.
Explanation	Drainage systems made of AISI304 or AISI316 grade stainless steel, siphon and duct production are made on a standard or project basis.

