

Stainless Steel Floor Sink, With Tray WTAC-30-F-11-KP

Description: It is a siphon-regulated, point-by-point wastewater evacuation product that can be cleaned to transfer wastewater formed in the installation facilities. This Drainage Systems product will prevent bacteria formation,

which will create a precaution from wastewater installation to odor and pest input.

Product Code : WTAC-30-F-11-KP

Areas of Use : Food Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Fat Food, Beverage, etc.)

Health Sector (Hospital, Laboratory, Pharmaceutical Production-Storage), Chemistry, Petro-Chemistry, Automotive, Cosmetics, Logistics and Transportation, Tourism Sectors, Shopping Malls, and Supermarkets

Technical Specifications

Automotive, Cosmetics, Logistics and Transportation, Tourism Sectors, Shopping Malls, and Supermarkets

With a fixed siphon, a graded pan with a mouse lock on the siphon, the first bend of the channel, and the

second bend where the upper grill is placed, reinforced with a 14x14 mm section from the bottom, full iron

plate, with anchorage and height adjustment parts.

 Dimensions
 : 300 x 300 x 200 mm

 Output Measure
 : DN100 (∅110 mm)

Odor Retention Water Depth : 60,00 mm

Solid Waste Holder Type : Bucket type strainer with basket.

Top Grid Type : Reinforced honeycomb type. (2.00 mm thickness)

Material : Reinforced honeycomb type. (2.00 mm thickness)

Completely made of AISI304 stainless steel, with the pan 2,00 mm, the upper grill 5,00 mm plate, and

the bottom reinforcements 25x5 mm sectioned flat steel.

Weight : 11,00 kg

Packaging: It is shipped in single packages with nylon shrink, in boxes, pallets, or cases, depending on the quantity.

Explanation : Drainage systems made of AISI304 or AISI316 grade stainless steel, siphon and duct production are made on

a standard or project basis.







